

**E-MOTION<sup>®</sup>M25**



Invacare Ltd  
 Unit 4 Pencoed Technology Park  
 Pencoed, Bridgend  
 CF35 5AQ  
 T: 01656 776222  
 E: ordersuk@invacare.com  
 www.invacare.co.uk

Please fill in all specifications with each order.


Account code

Customer order number

Company name

Address



- e-motion M25** **£5316**
  - Included as standard:
    - 2 e-motion drive wheels 22"
    - Speed: 6km/h Total diameter 550mm
    - Weight: Only 7.8 kg per wheel 24"
    - Brushed stainless steel push rims Total diameter 600mm
    - Charger 25" \*
    - Lithium-ion batteries in the Wheel hubs
    - Pneumatic tyres with puncture protection
  
- Ergonomic Control System (ECS)** 1592486 **£409**
  - Switches e-motion on and off
  - Two remote assistance levels
  - Roll back delay
  - Battery monitor
  - Self diagnosis
  
- Anti-tippers with jack-up function (pair)** 1489214 **£281**  
 NB Always use anti-tippers (Alber or existing)

**Mobility Plus Package**

Download from App Store or Playstore as an In-App purchase

- Remote control
- Increase speed to 8.5km/h
- Cruise control function,
- ECS functions
- Push counter - evaluates your driving behaviour during journeys



**Wheelchair details**

Wheelchair manufacturer (e.g.

Serial no

Year

Model (e.g. Compact)

Seat width



cm

Seat height (e.g.



cm

Armrest & Brake type

Degree of wheel

**(Drum brakes must be removed)**

\* Total diameter with Right Run 625mm, 615mm with Marathon Plus

Subject to Invacare's standard Terms and Conditions. Invacare reserve the right to alter product specification without prior notice.

**Brackets required for installation onto wheelchair**

- 1467178  **STD**
- Omit brackets  **-£67**

- Fitting on wheelchair at Invacare factory & delivery\*  **£75**

Wheelchair order number

- Collection & fitting to third party wheelchair & delivery\*\*  **£75 + £96**


- Fitting by trained dealer\*\*  **£0**

*\*Only when ordered with an Invacare wheelchair.  
 \*\*Mounting kits can only be sent to selected trained dealers.*

**Other**

- Equipped with vehicle retention system
- Rear wheel extension available

Available wheel position:



- 1=rear
- 2=centre
- 3=front

**E-MOTION<sup>®</sup>M25****Accessories****Push rims**

<input type="checkbox"/>	Stainless steel (standard)	1592526	£0
<input type="checkbox"/>	22" or 24" push rim cover, Tetra (pair)	1592527	£133
<input type="checkbox"/>	CarboLife Curve L Black Powder coated	1592528	£289
<input type="checkbox"/>	CarboLife Quadro Tetra-Gripp coated	1592520	£350

**Tyres (pairs)**

<input type="checkbox"/>	Schwalbe Rightrun (Standard) Black	1592530	£0
<input type="checkbox"/>	Schwalbe Marathon Plus Evolution with SmartGuard puncture protection, Black	1565894	£36
<input type="checkbox"/>	Pro Speed puncture-proof solid PU 1" Black (+ 300g per wheel, not available on 22" or 26")	1592532	£97
<input type="checkbox"/>	Puncture proof with inlay 1 3/8" (+ 500g per wheel, not available on 26")	1592533	£97

**Push rim covers (retrofit)**

<input type="checkbox"/>	Push rim cover 22"	1592425	£143
<input type="checkbox"/>	Push rim cover 24"	1592421	£143
<input type="checkbox"/>	Push rim cover 26"	1592426	£143

**Spoke Covers (pairs)**

<input type="checkbox"/>	22" spoke cover Design 'Comic'	1592266	£143
<input type="checkbox"/>	24" spoke cover Design 'Sphere'	1592268	£149
<input type="checkbox"/>	26" spoke cover, Design 'Sphere'	1592269	£154
<input type="checkbox"/>	24" spoke cover, Plain	1592553	£149

**Extra options**

<input type="checkbox"/>	Brake extension*	1467780	£30
<input type="checkbox"/>	Transport axle	1591362	£68
<input type="checkbox"/>	Ergonomic stubaxle	1591500	£131



Do you want to use both your standard and e-motion wheels in the future? If so, please order the retrofit stub axle.

Manual wheel axle retrofit for e-motion \* / \*\*

Retrofit, stub axle to 1/2" diameter  £103

\*If the manual wheels are used in combination with e-motion, these must be fitted with 1/2" stub axles, without drum brakes and 1" wide tyres.

\*\*If drum brakes are installed, these must be removed as they are not compatible with e-motion. Standard lever brakes are used instead.

\*maybe required depending on wheelchair type

Comments (mounting etc.)